

**HEXAGON NYLON INSERT LOCK NUTS - DIN 985**

**METRIC**

**GRADE**                      **304/A2**    **316/A4**

**DIAMETER**

	Part No.	PKT Qty	Part No.	PKT Qty
M2	3376	100		
M2.5	16506	100		
M3	3377	•	30187	100
M4	3378	•	16808	•
M5	3379	•	3735	•
M6	3380	•	3737	•
M8	3381	100	3738	100
M10	3382	100	3739	100
M12	3383	100	3740	100
M14			15792	50
M16	3384	50	3741	50
M18			19098	50
M20	3385	25	3742	25
M22			16351	25
M24			3743	25
M27			31082	20
M30			16352	10
M36			30184	5

**NOTE:** USE OF MOLY DI SULPHIDE GREASE IS RECOMMENDED WHEN USING NYLON INSERT LOCK NUTS.

**HEXAGON NYLON INSERT LOCK NUTS**

**BSW**

**GRADE**                      **304/A2**    **316/A4**

**DIAMETER**

	Part No.	PKT Qty	Part No.	PKT Qty
1/2x.750A/F	15626	100	15689	100
1/2	1672	100	1493	100

**NOTE:** USE OF MOLY DI SULPHIDE GREASE IS RECOMMENDED WHEN USING NYLON INSERT LOCK NUTS.

• PLEASE REFER TO BOOKLET AT BACK OF THE CATALOGUE FOR PACK QUANTITY.

**HEXAGON NYLON INSERT LOCK NUTS - STANDARD TYPE - NM/ME**

UNC				
GRADE	304/A2		316/A4	
	Part No.	PKT Qty	Part No.	PKT Qty
4-40	1661	•		
5-40	1664	100		
6-32	1665	100		
8-32	1666	•		
10-24	1667	•	1478	100
1/4	1668	•	5111	100
5/16	1669	•	5112	100
3/8	1670	100	5113	100
7/16			5114	100
1/2	1671	100	5110	100
5/8	1673	50	5115	50
3/4	1675	25	5116	25
7/8			16353	25
1	1677	25	14541	25
1.1/8			15191	20
1.1/4			14542	10
1.1/2			14543	5

NOTE: USE OF MOLY DI SULPHIDE GREASE IS RECOMMENDED WHEN USING NYLON INSERT LOCK NUTS.

**HEXAGON NYLON INSERT LOCK NUTS - STANDARD TYPE - NM/ME**

UNF				
GRADE	304/A2		316/A4	
	Part No.	PKT Qty	Part No.	PKT Qty
10-32	1678	100		
1/4	3907	100	1486	100
5/16	3909	100	1487	100
3/8	3911	100	1488	100
7/16			1489	50
1/2			1490	50
5/8			1491	25
3/4			1492	25
1			15190	25

NOTE: USE OF MOLY DI SULPHIDE GREASE IS RECOMMENDED WHEN USING NYLON INSERT LOCK NUTS.

**HEXAGON NYLON INSERT LOCK NUTS - THIN TYPE - NTE**

UNC		UNF		
GRADE	304/A2		304/A2	
	Part No.	PKT Qty	Part No.	PKT Qty
1/4	9680	100		
5/16	9681	100		
3/8	9682	100	5372	100
1/2			14559	50

NOTE: USE OF MOLY DI SULPHIDE GREASE IS RECOMMENDED WHEN USING NYLON INSERT LOCK NUTS.